

Titan Dimmable Drivers

Low-Profile Drivers



Product Overview

Accompanying the existing Titan range, this new 60W dimmable version builds upon the existing model while adding more functionality.

Still boasting a streamlined body and integrated JB4 ports, this new model has been developed to be compatible with most dimming switches, whether trailing or leading edge, as well as having a wide dimming range of 5% – 100%.

The Titan also features a wide range of safety features, such as protection from short-circuiting, overloading, and electrical surge.

Benefits

- Easy to use Just plug and play
- High efficiency
- Promotes inconspicuous installation

Key Features

- Depth of 16mm
- Integrated JB4 distributor ports
- 2m mains cable included

Technical Specification

- Short circuit & overload protection
- Surge and thermal protection

reclinical Specification		
	30W	60W
Rated Input Voltage (Vac)	220-240	220-240
Input Voltage Range (Vac)	198-264	198-264
Frequency (Hz)	50/60 ± 3%	50/60 ± 3%
Output Voltage (V)	24 ± 5%	24 ± 5%
Output Current (A)	1.25	1.25
Short Circuit Protection	Yes	Yes
Overload Protection	Yes	Yes
Thermal Protection	Yes	Yes
Surge Protection	Yes	Yes
Operating Temperature	-20°C to +40°C	-20°C to +40°C
Humidity	10% to 90%RH	10% to 90%RH
Mains Cable Length (M)	2	2
Number of JB4 Ports	6	10



Titan Dimmable Drivers

Low-Profile Drivers

New Technical Bulletin No. 096

Order Codes

Description	Order Code	Barcode		
Titan 30W Dimmable Driver	SE40899	5060522088066		
Titan 60W Dimmable Driver	SE40699	5060522086789		

Order Codes

Description	Dimensions (mm)	Weight (g)	IP Rating
Titan 30W Dimmable Driver	L158 x W60 x D16.5	128	IP20
Titan 60W Dimmable Driver	L217 x W56 x D16.5	150	IP20